

The Silver Service team are dedicated to providing responsive, fast and effective service. Our clients depend on us to have their shop fronts and entries opening for business and closing for security.

## PARAVENT WIDE BODY® by DYNAMIC CLOSURES

SIDE FOLDING PERFORATED ALUMINIUM CONCERTINA DOORS



Paravent Wide Body® (side folding door) is part of Dynamic Closures' WIDEBODY® range. Made with durable materials and a flexible design suitable for variety of internal or external situations. Paravent Wide Body is the perfect solution for:

- Commercial shop fronts
- Shopping centres
- Shop windows
- Retail outlets
- Serveries
- Counters
- Bars & restaurants
- Hotel kitchens
- Kiosks
- Patios
- Cafés

The robust aluminium perforated panel construction of the Paravent Wide Body curtain provides a breathable, functional and protective enclosure with contemporary style.

Paravent Wide Body is specially designed for ease of operation and offers a **quality and economical option**. Equipped with an inbuilt **premium locking and tracking system** and it has versatility to accommodate **smaller stacking sizes**.

# SPECIFICATIONS

## CURTAIN

Paravent Wide Body® curtain design shall incorporate **285mm O/A (w) x 101mm (h)** truss-like aluminium panels at top and bottom of enclosure, with a **240mm (w) x 2.6mm** aluminium infills with 4.5mm perforations providing 51% visibility. **Maximum height 5000mm.**

## CURTAIN EDGES

Shall be **32mm x 53mm** extruded vertical members, with top and bottom automatically retractable locking posts. One intermediate member shall be provided for every **3000mm** of opening. All intermediate members shall be fitted with adjustable, concealed drop bolts. Intermediate member spacing on counter applications. **1800mm** maximum.

## COLOURS

The standard finish for all visible aluminium components on Paravent Wide Body closures is a **clear anodised matt finish**. Optional extra powder coating in Dulux colour range is available.

## PARAVENT WIDE BODY 300MM PERFORATED PANEL

## CURTAIN WEIGHT

Curtain weight is **11 kg** per square metre. This may vary depending on locking post types and amounts.

## LOCKING

Lead posts shall be provided with cylinder locks and guards, operable from both sides. Master keyed cylinders (if required), shall be supplied by others. Top and bottom shoot bolt locking as standard. Dust proof floor sockets shall be provided. Electro – magnetic locking is available as an optional addition.

## HEAD TRACK

The track extruded aluminium **38mm (h) x 36mm (w)**. Curved tracks (where required) are supplied with a standard radius.

### STANDARD RADIUS:

**45 degree - 407mm and 559mm**

**90 degree - 407mm and 559mm**

To provide smooth and easy operation for **custom** curved applications, the radius must be nominated (minimum **1500mm**). For elliptical curves, a template must be provided to Silver Service Club prior to manufacture.



**OPTIONAL EXTRAS:**  
Egress Doors for emergency exits.  
Tapered openings.

## SMOOTH SAILING WITH SILVER SERVICE

As part of our commitment to providing superior service, we ensure that our clients will be smooth sailing with the Silver Service crew. **An After Hours Emergency number, 0401 333 776**, is offered to connect you directly to one of our technicians or sales staff to assist you anytime, anywhere.

Silver Service Club is continually researching and developing products and reserves the right to change specifications without notice.