

The Silver Service team are dedicated to providing responsive, fast and effective service. Our clients depend on us to have their shop fronts and entries opening for business and closing for security.

PRESTIGE SLIMLINE® by DYNAMIC CLOSURES

SIDE FOLDING POLYCARBONATE AND ALUMINIUM CONCERTINA DOORS



Prestige Slimline® (side folding door) is part of Dynamic Closures' SLIMLINE® range. Made with durable materials and a flexible design suitable for variety of internal or external situations. Prestige Slimline is the perfect solution for:

- **Commercial shop fronts**
- **Shopping centres**
- **Shop windows**
- **Retail outlets**
- **Serveries**
- **Counters**
- **Bars & restaurants**
- **Hotel kitchens**
- **Kiosks**
- **Patios**
- **Cafés**

The specially designed robust aluminium and polycarbonate panel construction of the Prestige Slimline curtain provides a strong protective barrier with easy operation and contemporary style.

Prestige Slimline offers a **quality and economical option**, equipped with an inbuilt **premium locking and tracking system**, and it has versatility to accommodate **smaller stacking sizes**.

SPECIFICATIONS

CURTAIN

Prestige Slimline® design shall incorporate **205mm O/A (w) x 101mm (h)** truss-like aluminium panels at top and bottom of curtain with **160mm (w)** wide clear polycarbonate infills with each individual panel encapsulated top and bottom with a vinyl retainer. **5000mm** maximum height.

CURTAIN EDGES

Shall be **32mm x 53mm** extruded vertical members, with top and bottom automatically retractable locking posts. One intermediate member shall be provided for every **3000mm** of opening. All intermediate members shall be fitted with adjustable, concealed drop bolts. Intermediate member spacing on counter applications **1800mm** maximum.

COLOURS

The standard finish for all visible aluminium components on Prestige Wide Body closures is a **clear anodised matt finish**. Optional extra powder coating in limited colours is available.

PRESTIGE SLIMLINE CONCERTINA DOOR



CURTAIN WEIGHT

Curtain weight is **11 kg** per square metre. This may vary depending on locking post types and amounts.

LOCKING

Lead posts shall be provided with cylinder locks and guards, operable from both sides. Master keyed cylinders (if required), shall be supplied by others. Top and bottom shoot bolt locking as standard. Dust proof floor sockets shall be provided. Electro-magnetic locking is available as an optional addition.

HEAD TRACK

The track extruded aluminium **38mm (h) x 36mm (w)**. Curved tracks (where required) are supplied with a standard radius.

STANDARD RADIUS:

45 degree - 407mm and 559mm

90 degree - 407mm and 559mm

To provide smooth and easy operation for **custom** curved applications, the radius must be nominated (minimum **1500mm**). For elliptical curves, a template must be provided to Silver Service Club prior to manufacture.

OPTIONAL EXTRAS:
Egress Doors for emergency exits.
Tapered openings.

SMOOTH SAILING WITH SILVER SERVICE

As part of our commitment to providing superior service, we ensure that our clients will be smooth sailing with the Silver Service crew. **An After Hours Emergency number, 0401 333 776**, is offered to connect you directly to one of our technicians or sales staff to assist you anytime, anywhere.

Silver Service Club is continually researching and developing products and reserves the right to change specifications without notice.



ADDRESS: 25A/1-3 ENDEAVOUR ROAD
CARINGBAH NSW 2229
PHONE: 02 9531 8542
AFTER HOURS: 0401 333 776
EMAIL: service@silverserviceclub.com.au